




Telescopic swing arm



Automatic load holding system



Extensions and lifting pads adapters



Wedge anchors and shims kit

DESCRIPTION

TECHNICAL FEATURES

- NEW : Telescopic swing arms
- 2 posts with synchronized hydraulic cylinders
- Without cable, chain and pulley
- No superstructure between posts
- Automatic load holding system (gravity stopper)
- Automatic swing arm restraint
- Symmetrical design

STANDARD EQUIPMENT

- 8 x socket adapters:
 - 4 x 2" height
 - 2 x 3" height
 - 2 x 6" height
- 4 x grooved lifting pad adapters (5" dia.)
- 16 x wedge anchors

OPTIONAL EQUIPMENT

- Power voltage 575/3/60,
- Jib crane :
 - 84" LG pole (2 000 lb capacity)
 - 96" LG pole (1 500 lb capacity)
 - 108" LG pole (1 000 lb capacity)
- Fork lift adapters
- Adjustable lifting pad adapter
- Folded lifting pad adapter
- Tripod high reach supplementary stand

SPECIFICATIONS

Capacity	14 000 lb
Lifting speed	86 SEC
Drive motor	2 HP
Power voltage	208-230/1/60
Lifting height	72"
Total height	153"
Shipping weight	3 600 LB