


Extra long telescopic swing arm



Automatic load holding system



Automatic swing arm restraint



Extensions and lifting pads adapters

DESCRIPTION

TECHNICAL FEATURES

- Telescopic swing arms EXTRA LONG
- 2 posts with synchronized hydraulic cylinder
- Without cable, chain and pulley
- No superstructure between posts
- Automatic load holding system (gravity stopper)
- Automatic swing arm restraint
- Symmetrical design

STANDARD EQUIPMENT

- 12 x 3"Ø socket adapters : 4 x 3" height / 4 x 6" height / 4 x 12" height
- 4 x grooved lifting pad adapters 5" dia. (5 000 lb capacity)
- 4 x anti-skid truck lifting pads
- 16 x wedge anchors

OPTIONAL EQUIPMENT

- Power voltage 575/3/60
- Jib crane : 84" LG pole (2 000 lb capacity) / 96" LG pole (1 500 lb capacity) / 108" LG pole (1 000 lb capacity)
- Socket and lifting pad adapters for light weight vehicles :
 - 8 x 2-1/2"Ø socket adapters : 4 x 2" height / 2 x 3" height / 2 x 6" height
 - 4 x reducing adapters for 5" pads
 - 4 x grooved lifting pad adapters 5" dia. (3 500 lb capacity),
- Tripod high reach supplementary stand.

SPECIFICATIONS

Capacity	16 000 LB
Lifting speed	100 SEC
Drive motor	2 HP
Power voltage	208-230/1/60
Lifting height	72 "
Total height	153 "
Shipping weight	4 350 LB